

3. (currently amended) A screeding method for ~~smoothing loose or plastic materials such as placed and/or poured, uncured concrete previously poured concrete placed on the ground or another support surface~~, the method comprising the steps of: mounting a striker and a rotatable, approximately 5.5 inch diameter, cylinder of between 8 and 12 feet in length in parallel on a screed frame; intertwining dual spiral flight coils of approximately 1-7/8 inches height and 4.5 inch spacing on an outside surface of the cylinder ~~from between ends of the cylinder to form an auger~~; positioning the striker spaced to one side of the auger and in parallel thereto; positioning the auger partially immersed in the ~~uncured-poured~~ concrete; and rotating the auger for removal of an excess portion of the poured concrete while drawing the auger and the striker in a lateral direction.

4. (cancelled) The screeding method of claim 3 comprising the further steps of fixing a pair of end blocks in ends of the auger; extending opposing rods from the end blocks longitudinally and engaging keyed apertures in the opposing rods with a motive means for rotating the auger.

5. (new) A screed assembly apparatus for smoothing poured concrete, said apparatus comprising: a screed frame, and mounted thereon, a striker for engaging and spreading the poured concrete, and a rotatable auger for moving the concrete longitudinally along the screed frame, the auger providing a pair of intertwined spiral flight coils each approximately 1-7/8 inches high, the striker spaced to one side of the auger and in parallel thereto; auger mounting means; and motive power means engaged for rotating the auger.

6. (new) The apparatus of claim 5 wherein the flight coils are spaced apart by approximately 4.5 inches